

MATERIAL SAFETY DATA SHEET (MSDS)

FIRST ISSUE DATE: June 08, 2000

Section 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **70079 Matrix – RESIN – Part A**

MFR'S NAME: Air Logistics Corporation, 925 North Todd Avenue, Azusa CA 91702

EMERGENCY PHONE: 800-424-9300 (CHEMTREC) GENERAL INFORMATION: 626-633-0294

Section 2: COMPOSITION, INFORMATION ON INGREDIENTS

INGREDIENT	%	CAS #	EXPOSURE LIMITS
Bisphenol A reaction products	<25	25085-99-8	N.E.
Polymers of epichlorohydrin	<40	028064-14-4	N.E.
Proprietary ingredients	>35	trade secret	N.E.

Section 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Novolac epoxy resin solution. Certain individuals may have pre-existing skin or respiratory conditions causing a sensitivity or allergy which manifests as various reactions. Heating or spraying this product or the mixed parts (A&B) increases potential health hazards. Burning will release harmful vapors.

POTENTIAL HEALTH EFFECTS:

EYE:

- May cause irritation.

SKIN:

- May cause irritation.

INGESTION:

- May inflame or damage the G.I. tract. Large quantities may be harmful.

INHALATION:

- May cause irritation.

CHRONIC EFFECTS:

- Repeated unprotected exposure may result in sensitization.

SIGNS & SYMPTOMS:

- Skin rash, irritation, reddening, or eczema; breathing difficulty or irritation.

Section 4: FIRST AID MEASURES

⇒USE APPROPRIATE BLOOD-BORNE PATHOGENS PROTECTIONS⇐

EYE:

- Hold eyelids apart and flood with large amounts of water. Get medical attention.

SKIN:

- Wipe off excess product. Wash thoroughly with soap and water. If irritation develops seek medical attention.

INGESTION:

- Do NOT induce vomiting unless directed to do so by medical personnel. Get medical attention.

INHALATION:

- Remove to fresh air. If problems develop or persist, get medical attention.

ATTENTION: No representation is made as to the accuracy or correctness of the information contained herein, other than to state that it is presented by this organization in good faith and we believe it to be correct and accurate per the limits of our understanding and training as of the date of first publication. The user or handler of this product is warned to take the most conservative and safest interpretation possible of all information contained herein and to use the most extreme personal protection measures and exposure limitations prudently dictated by the specific usage or handling situation, this MSDS information and good industrial safety and hygiene practices.

Section 5: FIRE FIGHTING MEASURES

FLASH POINT: 177°C (350°F) UEL/LEL: N.D.A. VAPOR DENSITY: N.D.A.
NFPA FLAMMABILITY RATING: 1 AUTOIGNITION: 300°C (570°F)
COMBUSTION PRODUCTS: CO, CO₂, NO_x, & misc. hydrocarbons
SPECIAL HAZARDS: Burning may cause extra health and safety risks. Pre-sensitization to epoxy.
EXTINGUISHING MEDIA: Use foam, CO₂, dry chemical, water fog.
FIRE FIGHTER INSTRUCTIONS: Stay upwind. Wear at least full turnout gear and SCBA.

Section 6: ACCIDENTAL RELEASE MEASURES

Isolate spill. Keep out of sewers and drains. Vacuum, scoop or absorb spill. Clean up residue with soap and water.

Section 7: HANDLING AND STORAGE

Avoid skin and eye contact. Do not breath product mist or heated vapors. Wash thoroughly after handling. Never eat or smoke around product.

Store in original sealed containers in a cool, dry ventilated storage area.

Section 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

GENERAL: Provide ventilation and protect body from physical contact.
EYE/FACE: Safety glasses, minimum.
SKIN: Butyl or nitrile chemical resistant gloves recommended.
RESPIRATORY: Not required where mists or heated vapors won't occur. If required, use at least NIOSH-approved cartridge respirator with organic vapor/HEPA filter cartridges.
OTHER: Decontaminate or discard clothing and footwear that have come in contact with raw product.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: paint-like syrup ODOR: slightly sweet PHYSICAL STATE: liquid
pH: N.D.A. VAPOR PRESS: N.D.A. VAPOR DENSITY: N.D.A. SPECIFIC GRAVITY: 1.25
BOILING PT: N.D.A. MELT PT: N/A SOLUBILITY IN H₂O: slightly

Section 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY: Material is stable with no known conditions to avoid.
INCOMPATIBILITY: Strong acids, caustics, oxidizers and epoxy hardeners in uncontrolled conditions.
HAZARDOUS POLYMERIZATION: Will not occur.
HAZARDOUS DECOMPOSITION: None known, other than Sec. 5's Combustion Products.

Section 11: TOXICOLOGICAL INFORMATION

N.D.A.

ATTENTION: No representation is made as to the accuracy or correctness of the information contained herein, other than to state that it is presented by this organization in good faith and we believe it to be correct and accurate per the limits of our understanding and training as of the date of first publication. The user or handler of this product is warned to take the most conservative and safest interpretation possible of all information contained herein and to use the most extreme personal protection measures and exposure limitations prudently dictated by the specific usage or handling situation, this MSDS information and good industrial safety and hygiene practices.

Section 12: ECOLOGICAL INFORMATION

N.D.A.

Section 13: DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable laws and regulations.

Section 14: TRANSPORT INFORMATION

DOT: Not Regulated
IATA: Not Regulated

Section 15: REGULATORY INFORMATION

OSHA 1910.1200: listed	DOT 172.101: not listed	CERCLA RQ: not listed
CLEAN AIR 112(b): not listed	TSCA: listed	STORMWATER RUNOFF: not listed
SARA 313: not listed	SARA TPQ: not listed	SARA PRIORITY (PC): not listed
CA PROP. 65: not listed.	RISK MGMT: not listed	RCRA Waste Number: none
VOC %: zero		

Section 16: OTHER INFORMATION

NFPA:
HEALTH 1 FIRE 1 REACTIVITY 0 OTHER N/A

ABBREVIATIONS: N/A = not applicable; N.D.A. = no data available; N.E. = not established

END OF MSDS